PT Platforms and GK Indicators



The perfect pairing of Adam Equipment's PT platforms and GK indicators for the most accurate and feature friendly combination. The PT bases offer solid mild steel construction with reinforced supports for a better base assembly and a diamond checkered plate for extra grip. A direct access to the junction box from above and over 10 feet of cable make for one of the most flexible bases around.

The GK indicator offers a range of features including check weighing, percentage weighing, parts counting and dynamic weighing combined with a bright backlit display with capacity tracker, a rechargeable battery, and full numeric keypad. For check weighing applications the built in amber, green and red indicators show the operator if the sample is under, over or at the preset limits.

With over three decades of experience in the production of weighing equipment you can trust Adam for quality products that offer a range of features designed for a many different applications.
















PT Series

PT series of floor scales feature a low profile design for easy loading and unloading. The range incorporates a non-slip checkered plate for added grip.

Heavy duty rubber feet support the four loadcells ensuring quality and longevity of the bases. With a number of different configurations and capacities there is a PT based that will meet all your industrial applications.

Features

- Adjustable levelling feet
- 4 loadcell construction
- 10 feet of loadcell cable
- Heavy duty rubber feet



GK Indicator

With a number of weighing modes and units the GK indicators can be adapted to a wider range of applications. A large backlit display is easy to read with a capacity tracker to help protect from overloading and the colored LED indicators are ideal for check weighing applications to measure underweight, overweight and acceptable limits. With standard RS-232 interface for computers and printers, rechargeable battery and AC adapter powered, and full numerical keypad, the GK offers the most value for an indicator.

Features

- Full tare range
- Accessible internal rechargeable battery
- Large backlit LCD display with capacity tracker
- Battery operation with auto-off to save battery life
- Parts counting with freely selectable sample sizes
- Check weighing LED lights to show acceptable limits
- · Automatic accumulation
- Bi-directional RS-232 output for connection to computers and printers

Technical Specifications

PT Series

Model	Maximum Scale Capacity (lb/kg)	Platform Size (in/mm)	Height (in/mm)	Net Weight (lb/kg)	Cable	Construction
PT 112	2500lb / 1000kg	47in x 47in 1200mm x 1200mm	4in / 100mm	264lb / 120kg	10ft / 3m long	Mild Steel
PT 312-5	5000lb / 3000kg	00kg 47in x 47in 1200mm x 1200mm 4in / 100mm 264lb		264lb / 120kg	10ft / 3m long	Mild Steel
PT 312-10	10000lb / 4500kg	47in x 47in 1200mm x 1200mm	4in / 100mm	264lb / 120kg	10ft / 3m long	Mild Steel

GK Indicators

Model	Sensitivity Loadcells		Zero input range	Signal Range	Weighing Units	Readability
GK	Up to 1:30,000	Up to 4 x 350ohm loadcells	0 - 10mV	0 - 40mV	g, kg, lb, oz, lb:oz	Selectable

Accessories

- Item No. 9071 PT 12R Ramp Option (47" x 33" x 5" / 99lb)
- Item No. 0000 In--use cover for GK

