

# LPS150 / LPS400

## Portable Shipping Scale



- Accuracy 0.1% of full scale
- Capacity

   150 lb (68 kg) and 400 lb (181 kg)
- Construction

   Low profile stainless steel
   platform with mild steel understructure, and
   stainless steel/ABS indicator with wall
   bracket and desk mount included.
- Platform Size

   15" L x 12" W x 1" H

  380 mm (L) x 305 mm (W) x 27 mm (H)
- Protocol

   — Standard NCI interfaces to
   most common shipping software, including
   UPS™ Worldship Online and FedEx®.
   Not legal for trade
- Display

  Five 0.625" digits LCD
- Power

  Battery or AC power
- Operator Keys

   On/Off/Zero, Tare, Units (lb/kg), Hold/Print

VALUE IN WEIGHING

### LPS150 / LPS400 Portable Shipping Scale

#### **Features**

LPS150 / LPS400 scales are particularly suited to shipping/warehouse applications and general purpose weighing. These are very affordable scales with accurate weights up to 400 lbs.

The dual power modes (battery and AC adapter) enable portability or permanent installation (both included).

A large, simple to read display can be wall or stand mounted for easy visibility and the large keyboard switches work with gloved hands (wall and desk bracket included).

The indicator cable is a coil style for durability and easy extension.

The LPS Series features RS-232 interface that can transmit and receive using a demand type protocol.

Scale comes standard with NCI protocol and interfaces to most common shipping software, including UPS™ Worldship Online and FedEx®.

A durable low profile platform allows for easy weighing. The LPS Series is a low cost yet versatile and portable scale.

Application - Shipping/Receiving

Mailroom

Manifest Systems

General Purpose Weighing

Not legal for trade



### **Specifications**

**Capacity**– 150 lb x 0.05 lb (68 kg x .02 kg) 400 lb x 0.2 lb (181 kg x 0.1 kg)

Platform Size- 15" L x 12" W x 1" H 380 mm (L) x 305 mm (W) x 27 mm (H)

Indicator- 6.5" L x 3.2" H x 1.2" W 164 mm (L) x 81 mm (H) x 29 mm (W)

Display- Five 0.625" digits LCD



RS-232- 10' interface cable (DB-9) (included)

Keyboard- On/Off/Zero, Tare, Units (kg.lb), Hold/Print

Units- lb, kg, lb/oz

**Power**– Four (4) AAA batteries or 6 VDC, 500mA adapter (both included)

Battery Life-20 hours

Operating Temp- 41° F to 95° F (5° C to 35° C)

Packaging Dimensions-

Scale: 17" L x 15" W x 2.3" H 450 mm (L) x 400 mm (W) x 60 mm (H)

Shipping Weight- 11 lb (5 kg)

**Certifications**– Full FCC compliance, UL/CUL power adapter



Salter Brecknell Weighing Products

1000 Armstrong Dr., Fairmont, MN 56031 Toll free: 800-637-0529, Tel: 507-238-8702 Fax: 507-238-8271

e-mail: sales@salterbrecknell.com www.salterbrecknell.com

